



## Sequential Module for dust sampling

# Sentinel PM



### Main Characteristics:

- **Certified by TÜV in accordance with the EN12341 and DM60 norms**
- **Main applications:**
  - Total particulate matter
  - 10, 2.5, 1 micron fractions (PM10, PM2.5, PM1)
  - Heavy metals
- **16 filter capacity**
- **Reduced dimensions and weight**
- **Operation box for outdoor use with IP 55 protection grade**
- **Fixable to wall**
- **Forced ventilation circuit for safeguarding the samples' integrity**

The SENTINEL PM module combined with the atmospherical sampler Charlie, allows the automated and sequential collections of the atmospherical particulate matters on 47 mm diameter filtering membranes, which are contained in appropriate filterholder cassette.

The 16 filter capacity and the particular realization of a removable system, permit the filter recovering and replacing without interrupting the sampling, and so without predeterminating the periods of time of its operation.

The straight route of the suction tube and the separation of the permanence zone of the filters from the internal or radiant source of heat allows gaining and maintaining the integrity of the samples.



Thanks to its reduced dimensions and weight, Sentinel PM is easy to transport and integrate in the monitoring cabins.

The modularity of the sampling head allows choosing the desired impactor type to operate in accordance with the EN 12341 and USEPA 40 CFR Part 50 methods.

### Technical Characteristics:

Used supports	Membrane filters 47 mm diam
Autonomy	16 filters
Power supply	220 V 50 Hz
Dimensions mm (b x b x h)	400 x 250 x 600
Box	In fire painted steel
Weight kg	13
P/N of article	AA99-013-0005SP
Roof crossing kit	AA99-013-9906SP

TCR TECORA s.r.l. Via Alessandro Volta, 22/24 - 20094 Corsico (MI) Italy - Tel. 02 4505501 Fax. 02 48601811 - www.tecora.it e-mail: tcrtec@tecora.it

Product Data Immission Line 2.008.1 Ed. 0 02/04 - Technical specifications may change without previous warning