Accessories for Ambient Sampling

Sampling Heads

Portable tripod for sampling heads

Equipped with 47 mm diam. membrane cassetteholder, usable with all types of heads.



PM10 LVS Head

Approved

Only PM10 2.3 m³/h Heads Usable either with BRAVO constant flow rate sampler or with the most sophisticated CHARLIE constant flow rate sampler.

The sampling head is not included in delivery.

Cassettes for membranes Diam. 47 mm

To use in filterholders for particulate matter.



Package of 5 cassettes P/N AA99-010-9905CR Package of 20 cassettes P/N AA99-010-9906CR

Set of 8 nozzles for LVS head transformation



PM10 for 2.3 m³/h flow rate
P/N AA99-010-0030KP
PM10 for 1 m³/h flow rate
P/N AA99-010-0031KP
PM 2.5 for 2.3 m³/h flow rate
P/N AA99-010-0035KP
PM 2.5 for 1 m³/h flow rate
P/N AA99-010-0036KP

PM10 US EPA Head

(40 CFR Part 50)

for 1 m³/h sampling flow rate.



P/N AA99-010-0011SP

WINS PM2.5 US EPA Impactor (40 CFR Part 50)

for 1 m³/h sampling flow rate. To obtain the PM 2.5 fraction, must be used in PM 10 head series.



P/N AA99-010-0001SP

Ed. 1 08/06 - Technical specifications may change without previous warning

2.101.1

Product Data Immission Line

PM1 LVS Head

for 2.3 m³/h sampling flow rate.

Furnished with 16 nozzles, not compatible with the LVS PM10 and PM2.5 models.



P/N AA99-010-0027SP

Fax. 02 48601811 - www.tecora.it e-mail: tcrtec@tecora.ir - Tel. 02 4505501 Corsico (Mi) Italy 20094 22/24 -Via TCR TECORA S.r.l.



According to the EN 12341 norm: ONLY PM10 for 2.3 m³/h flow rate

According to the EN 14907 norm:

ONLY PM 2.5 for 2.3 m³/h flow rate

P/N AA99-010-0020SP

P/N AA99-010-0021SP

P/N AA99-010-0025SP

P/N AA99-010-0026SP

PM 2.5 for 1 m³/h flow rate

PM10 for 1 m³/h flow rate